

# **STATICO**

## **TOPICAL ANTISTAT \* EFFECTIVE CLEANER \* DUST ELIMINATOR**

**STATICO** has been formulated for use in STATIC SENSITIVE AREAS. **STATICO** eliminates static charges and prevents buildup of triboelectric charges by increasing surface conductivity for extended periods of time.

Independent Laboratories have tested **STATICO** under the most stringent conditions. These tests were conducted at 72°F and 12% relative humidity. **STATICO** exceeds the standards set forth in MIL-B-81705B, ASTM-D-257-80, Electronic Industry 1S-5, and NFPA-99.

By simply spraying, dipping, wiping or damp mopping almost any surface can be static free. Because **STATICO** contains no solvents or abrasives and is nonflammable it can be used on any surface not affected by water.

<b>Procedure Floors:</b>	<b>Carpets, Fabrics, Tables, Chairs, Bench top, Computer Work Areas:</b>
<b>For light cleaning and static prevention – damp mop, do not rinse. Repeat process as necessary after floor scrubbing or striping</b>	<b>Spray with a fine mist, do not soak. Treat heavy traffic areas more often as part of ESD Program</b>

## **STATICO SPECIFICATIONS**

COMPOSITION	HIGH MOLECULAR WEIGHT TOPICAL ANTI-STAT, WATER BASE
PHYSICAL FORM	LIQUID
COLOR	CLEAR
FLASH POINT	NONE
EXPLOSION HAZARD	NONE
SPECIFIC GRAVITY-REGULAR	1000 @ 60°F
SPECIFIC GRAVITY-CONCENTRATE	1002 @ 60°F
WEIGHT	1 gallon = 8.33 lbs.
ODOR	NONE
PH REGULAR	7.71
PH CONCENTRATE	7.98
CONCENTRATE DILUTION	1oz to 32oz or 4oz per gallon
STATIC DECAY RATE - SECONDS MIL-B-81705-B AT RELATIVE HUMIDITY 12%, 72° F	.01 seconds to drain 5KV to 0
SURFACE RESISTIVITY TEST MODEL 801 PROBE A.S.T.M. D-257 RELATIVE HUMIDITY 12%, 72° F	4.6 x 10 <sup>9</sup> OHM

\*STATICO HAS BEEN TESTED BY INDEPENDENT LABORATORIES FOR SURFACE RESISTIVITY USING ASTM-D-257-80, AND STATIC DECAY USING MIL-B-81705-B, ELECTRONIC IS-5 AND NFPA-99. STATICO COMPLIES AND EXCEEDS ALL TESTS REQUIRED BY FEDERAL STANDARD TEST METHODS.

**.... From Best Pak Company where quality still comes first  
Static Control Division**

**6865 Downs Street Worthington, Ohio 43085  
614-885-7527 / 877-885-7527 Fax: 614-888-3094**

<http://www.bestpakcompany.com/> <mailto:esd@BestPakCompany>