

Best Pak Company P.O. Box 527 Worthington, Ohio 43085

Phone: 614-885-7527 / 877-885-7527 Fax: 614-888-3094

Email: <mailto:info@BestPakCompany.com>

Topical Antistats



STATICO

READY TO USE

TOPICAL ANTISTAT-EFFECTIVE CLEANER-DUST ELIMINATOR

STATICO has been formulated to eliminate static charges and prevent buildup of triboelectric charges by providing surface conductivity on non-conductive surfaces for extended periods of time.

Independent Laboratories have tested STATICO under the most stringent conditions. These tests were conducted at 72° F and 12% relative humidity. STATICO exceeds the standards set forth in MILB-81705B, ASTM-D-257-80, Electronic Industry IS 5.

TEST RESULTS AVAILABLE UPON REQUEST.

By spraying, dipping, wiping or damp mopping almost any surface can be static free. Because STATICO contains no solvents or abrasives and is non-flammable, it can be used on any surface not affected by water. Also available in economical concentrate.

STATICO SPECIFICATIONS

TYPE: High molecular weight topical antistat, water base

APPEARANCE: clear liquid

FLASH POINT: none

EXPLOSION HAZARD: none

SPECIFIC GRAVITY: 1.00 @ 60deg/60degF

WEIGHT: 1 gal=8.33 lbs

ODOR: none

house dilution 7.71

STATIC DECAY RATE-seconds:0. 01 Sec + 5.0KV

REL HUMIDITY: 12%, 72F

CONDUCTIVITY: static dissipative

CONCENTRATE DILUTION: 1 oz. to 32 oz., 4oz. to 1 gallon

STATICO #2

TOPICAL ANTISTAT FOR FOOD CONTACT AREAS

STATICO #2 offers both static control and food contact certification.

*Meets FDA Title 21, par. 178.3130 for N,N-Bis (2 hydroxyethyl) dodecanamide, an antistatic agent intended for contact with honey, chocolate, liquid sweeteners, condiments, flavor extracts, and liquid flavor concentrates, grated cheese, light and heavy cream, yogurt and any food type that is a dry solid with the surface containing no free fat or oil.

*Safe and effective for house wares applications: polyethylene and/or polypropylene straws and polystyrene cup.

*Does not affect polyethylene film quality or clarity at recommended dilution.

STATICO #2

SPECIFICATIONS

TYPE: Topical antistat for food contact surfaces

APPEARANCE: clear liquid

SPECIFIC GRAVITY: 0.99

BOILING POINT: 212deg F

FLASH POINT: none

DECAY RATE: less than 1

second

COVERAGE PER QUART:

4000 sq.ft.

CONDUCTIVITY: static

dissipative

614-885-7527 877-885-7527 Fax: 614-888-3094
www.bestpakcompany.com Email: <mailto:info@bestpakcompany.com>

**STATICO™ AE
TOPICAL ANTISTAT**

Formulated to eliminate static charges on carpets, upholstery, and fabrics. Effectively prevents triboelectric charge buildup by increasing surface conductivity for an extended period. STATICO AE contains no solvents or abrasives and is non-flammable. Apply by spraying with a fine mist - do not soak. Heavy traffic areas may need treatment more often.

**STATICO AE
SPECIFICATIONS**

TYPE: water based topical antistat
APPEARANCE: clear liquid
FLASH POINT: none
SPECIFIC GRAVITY: 1.02
WEIGHT PER GALLON: 8.34
ODOR: none
pH: 7.21
CONDUCTIVITY: static dissipative

ELIMSTAT® ATS

Concentrated Topical Antistat-Prevents Dust Deposits-Controls Static Charges on Insulating Surfaces

Water based ELIMSTAT ATS is formulated for use Where static electricity needs to be controlled. ELIMSTAT ATS will make any surface it is applied to static dissipative and eliminate static charges in static sensitive environments. By eliminating static charges and controlling static generation, nuisance problems such as static cling as well as problems associated with manufacturing plastics and damage to electronic components are overcome. ELIMSTAT ATS is supplied as a concentrate for economical use. Dilute to 8 ounces per gallon of water for long-term effectiveness. ELIMSTAT ATS is non-flammable and fully biodegradable.

**ELIMSTAT®ATS
SPECIFICATIONS**

TYPE: water based topical antistat
APPEARANCE: clear liquid
FLASH POINT: none
SPECIFIC GRAVITY: 1.04
WEIGHT PER GALLON: 8.36
ODOR: none
pH: 7.8
CONDUCTIVITY: static dissipative